

Carrier CORPORATION, Syracuse, New York

OPERATION AND MAINTENANCE

of

REFRIGERATION PLANT

installed at

ALTITUDE WIND TUNNEL

CLEVELAND, OHIO



Government Contract Number NAW 1460
Pittsburgh-Des Moines Steel Co. No. P-43
Carrier Corporation Number 2N 1135

Copyright — 1944
CARRIER CORPORATION
Syracuse, N. Y., U. S. A.

BOOK No. 1

INDEX

	Page
SECTION ONE	
REFRIGERATION SYSTEM IN GENERAL.....	1
SECTION TWO	
REFRIGERANT CYCLES	3
Holding Cycle	3
Precooling Gasoline with F-12 in Storage.....	3
Transfer of F-12 from Storage to Flash Cooler.....	4
Precooling Gasoline with F-12 in Flash Cooler.....	4
Cooling Cycle — Altitude Tunnel.....	5
Defrosting Cycle	5
Transfer of Refrigerant from System to Storage Tank	6
SECTION THREE	
OTHER CYCLES	7
Oiling System Cycle	7
Purge Recovery Cycle.....	9
SECTION FOUR	
FUNCTIONS OF COMPONENT PARTS.....	15
Centrifugal Compressor	15
Condenser	15
Economizer	16
Flash Cooler	16
Suction Dampers	16
Temperature and Protective Controls.....	17
Heat Exchanger	18
Liquid Distribution Valves	18
Hot Gas Defrosting Valve	19
Float Tank	19
Liquor Pumps	19
Pump-out Compressors	20
Oil Still	20
Standard Recovery Unit	21
Special Low Temperature Purge.....	21
Gasoline Cooler	21
SECTION FIVE	
OPERATING PROCEDURE	31
Start Up	31
Operation of System.....	32

Shut Down	51
Leak Testing	52
Charging	54
Removing Refrigerant	54
SECTION SIX	
ROUTINE MAINTENANCE	57
Refrigeration Machine Assembly	57
Motors	57
Gears	57
Condensers	57
Compressors	57
Economizer	58
Defrosting Valves	58
Suction Dampers	58
HEAT EXCHANGER	58
Distribution Valves	58
Pot Strainers	59
Oil Still	59
LIQUOR PUMPS AND LINES	59
LIQUID LINE FILTER	60
PUMP-OUT COMPRESSORS	61
Service Difficulties	65
PURGE SYSTEMS	71
Standard Purge and Dryers	71
Low Temperature Purge and Dryers	72
PUMP-DOWN AND DEHYDRATION	72
SECTION SEVEN	
TROUBLE DIAGNOSIS CHART	73
SECTION EIGHT	
LIST OF EQUIPMENT	79
SECTION NINE	
CARRIER REPLACEMENT PARTS	83
1. Centrifugal Compressor	83
2. Condenser	84
3. Economizer	84
4. Defrosting Valve	84
5. Liquid Distribution Valve	84
6. Pump-out Compressor	84
7. Coils and Evaporator Piping	84

INDEX OF DRAWINGS AND CHARTS

	Page
DRAWING No. 1 — Refrigeration Machine Room Layout (D737-9245)	2
FLOW CHART No. 1	between 6 and 7
FLOW CHART No. 2	" "
FLOW CHART No. 3	" "
FLOW CHART No. 4	" "
FLOW CHART No. 5	" "
FLOW CHART No. 6	" "
FLOW CHART No. 7	" "
FLOW CHART No. 8 — Compressor Oiling Cycle	between 14 and 15
FLOW CHART No. 9 — Purge Recovery Cycle	" "
DRAWING No. 2 — 50 HP Condensing Unit Assembly (SD7G8-358-1)	22
DRAWING No. 3 — Gasoline Cooler Assembly (D737-9573)	24
THERMODYNAMIC PROPERTY TABLES — Freon 12	27-28
PSYCHOMETRIC CHART for Low Temperatures	29
PSYCHOMETRIC CHART for Normal Temperatures	30
CURVE No. 1 — Oil Absorption of Freon 12	33
CURVE No. 2 — Evaporator Performance — 5,000 Ft. Altitude	34
CURVE No. 3 — Evaporator Performance — 10,000 Ft. Altitude	35
CURVE No. 4 — Evaporator Performance — 15,000 Ft. Altitude	36
CURVE No. 5 — Evaporator Performance — 20,000 Ft. Altitude	37
CURVE No. 6 — Evaporator Performance — 25,000 Ft. Altitude	38
CURVE No. 7 — Evaporator Performance — 30,000 Ft. Altitude	39
CURVE No. 8 — Transfer Liquor Pump — Characteristic Curve	40
CURVE No. 9 — 75 and 60 HP Liquor Pump	41
CURVE No. 10 — Pump Capacities — GPM at Various Speeds	42
CURVE No. 11 — Centrifugal Machine Performance	43
LOG SHEET No. 1 — Compressor Log	44
LOG SHEET No. 2 — Control Room Log	45
LOG SHEET No. 3 — Engineer's Daily Report	46
CURVE No. 12 — Liquor Pump Operating Pressures	48
CURVE No. 13 — Effects of Air in System	49
DRAWING No. 4 — Refrigerating Machine Assembly (D737-4243)	following page 88
DRAWING No. 5 — 17S44 Compressor Assembly (17S44-494)	" " 88
DRAWING No. 6 — Special 17R9 Condenser Section and Baffle Location (D737-3403)	" " 88
DRAWING No. 7 — Centrifugal Control Panel Assembly (D737-4704)	" " 88
DRAWING No. 8 — Economizer General Assembly (D737-4415)	" " 88
DRAWING No. 9 — Switching Valve and Condenser Float Chamber (D737-4430)	" " 88
DRAWING No. 10 — Switching Valve Assembly on Economizer (D737-4826)	" " 88
DRAWING No. 11 — Condenser Float Assembly (D737-4830)	" " 88
DRAWING No. 12 — Automatic Control Piping Economizer Switching Valve (D737-42719)	" " 88
DRAWING No. 13 — Suction Damper General Assembly (D737-4116)	" " 88
DRAWING No. 14 — Pneumatic Control Piping (D737-41057)	" " 88
DRAWING No. 15 — Piping Outside Tunnel (D737-9014)	" " 88
DRAWING No. 16 — Evaporator Coil Assembly (D737-4150)	" " 88
DRAWING No. 17 — Assembly Liquid Line Control (D737-4764)	" " 8
DRAWING No. 18 — Schematic Diagram of Liquid Distribution Valve Assembly (D737-42624)	" "
DRAWING No. 19 — Defrosting By-pass Valve Assembly (D737-4676)	" "
DRAWING No. 20 — Float Tank Assembly (D737-4654)	" "

Book No. 2 is a separate and complete collation of the catalogues and instruction leaflets furnished by all of the vendors who supplied equipment used on the Carrier Contract. The book is bound in a separate cover.

BOOK No. 2

INDEX

TITLE	SECTION
Alco Valve Co.	1
Blackmer Pump Co.	2
Brown Instruction Co.	3
Buffalo Forge Co.	4
A. W. Cash Co.	5
Cutler Hammer, Inc.	6
Gould Pumps, Inc.	7
Hagan Corporation	8
Henry Valve Co.	9
Merco-Nodstrom Valve Co.	10
Mercoid Corporation	11
Minneapolis Honeywell Regulator Co.	12
Mueller Brass Co.	13
William W. Nugent and Co., Inc.	14
H. A. Phillips and Co.	15
Pomana Pump Co.	16
Powers Regulator Co.	17
Republic Flow Meter Co.	18
Taco Heater Co.	19
Taylor Instrument Co.	20
Westinghouse Electric and Manufacturing Co.	21

SECTION ONE

GENERAL DESCRIPTION OF SYSTEM

The refrigerating system serving the Altitude Tunnel is a combination flash and flooded system in that the latent heat of the liquid is utilized in absorbing the heat in the tunnel and because there is an excess of sub-cooled refrigerant circulated through the evaporator at all times. This system is comparable to a flash cooler type plant having a main flash cooler in which the refrigerant is 100% sub-cooled before it is pumped through the evaporator by liquor pumps.

Except for a few special auxiliaries, the system is basically similar to any flooded system. Special features, such as hot gas by-pass valves, float tank, liquid distribution valve, etc., are necessary for the special functions of de-frosting and proper distribution of refrigerant with variable flow. Essentially, the system includes the compressors or heat pumps, condensers, economizers, flash cooler, pumps and evaporator. The basic refrigeration cycle is as follows: Refrigerant vapor from the evaporator and from the flash cooler is drawn through throttling or suction dampers into a suction manifold from which the fourteen four-stage compressors pump the gas and compress this vapor before discharging it to the water cooled condensers. The gas in the condensers is at a condition of temperature and pressure which will produce condensation, after which the condensed gas or liquid passes through a high side or a condenser float valve into the two stage economizers or is returned directly to the flash cooler depending upon the operating conditions.

If evaporator conditions are such that the liquid enters the economizers the refrigerant is then flashed through two stages of pressure in which it is sub-cooled and the excess vapor returned to the 2nd and 3rd stages of the compressor. Liquid leaving the economizer, therefore, is at a temperature corresponding to the 1st stage discharge temperature of the machine. As it leaves the low stage of the economizer it flashes once again to evaporator temperature and the flash gas returns to the compressor. Sub-cooled liquid refrigerant is circulated by two main liquor pumps to the evaporator in the tunnel. Distribution of the liquid refrigerant to the various levels of the evaporator is maintained in the correct proportions by liquid distribution valves located at each level of the tunnel. These liquid distribution valves or weighted check

valves, have counterweights which compensate for the static head at each level and thus admit the correct amount of refrigerant to each level regardless of quantity being circulated.

After entering the evaporator, approximately 60% of the refrigerant is evaporated and returned as vapor to the flash cooler while the excess liquid returns through the same lines.

During the de-frosting cycle, the hot gas from the compressor by-passes the condenser and is introduced to the flash cooler through special de-superheater tubes immersed in the refrigerant. The heat of compression, therefore, is used to heat the refrigerant in the cooler, thus raising the vapor pressure until there is a reversal of flow. Liquor pumps, of course, are shut down; consequently, hot gas flows in a reverse direction through the suction line to the evaporator where it is condensed and the condensed liquid returns through the liquid line to the float tank. In this vessel a special modulating float valve maintains a definite suction pressure on the evaporator. This supplementary pressure assists in returning the condensed refrigerant to the cooler. The mixture, returning from the evaporator, separates in the float tank where excess gas is drawn off to the suction header through the defrost line. During the de-frosting cycle, the condensed liquid by-passes the liquid distribution valves at each level of the tunnel.

After de-frosting has been completed, the liquor pumps are again put into operation, the hot gas by-pass valve on the condenser is closed and cooling of the refrigerant takes place in the conventional manner.

The auxiliary equipment required to make this system more flexible and to maintain proper conditions during shut down and during service, will be explained in more detail in another section of this Manual.

